



Power Strip XO CCV5RD-6T1-C (EU)

1x CEE16A IN - 6x powerCON TRUE1® TOP OUT

Power Strip Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions. 1x CEE16A In and up to 6x powerCON® TRUE1® TOP Out.

Features & Benefits

- ✓ Extreme robust and safe EASYLEN® housing with leather grain texture
- ✓ Mains receptacles CEE16A In & daisy chaining and highly reliable NEUTRIK® powerCON® TRUE1® TOP Out
- ✓ Flame retardant (UL94-V0) and non-conductive housing material
- ✓ High outdoor protection (IP65, IK, ..)
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options

Applications and markets

- ✓ Main markets: Professional video walls, event lighting, pro-audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

Ordering Information

| Article name | Details | Order code |
|--------------|---|------------|
| CCV5RD-6T1-C | IN: 1xCEE16A - OUT: 6x powerCON® TRUE1® TOP | 1027454 |

Technical Information

| Product | |
|----------------|--------------------------|
| Input device | 1 x CEE16-5 |
| Output device | 6 x powerCON® TRUE1® TOP |
| Daisy chaining | none |

| Electrical | |
|---------------------------------------|----------------------|
| Contact resistance / protection class | Protection class II |
| Dielectric strength | 0.5 kV / mm |
| Rated voltage | 400 V AC |
| Rated Current | 16 A |
| Number of electrical contacts | 4 + PE |
| Phases | multi-phase (3+N+PE) |

| Mechanical | |
|-------------------------|--|
| Dimensions | 489.6 x 92 x 117.2mm |
| Conductor cross section | 2.5 mm ² |
| Weight | 2.1 kg |
| Mounting options | Truss clip, truss clamp, mounting wholes for pegging or suspension |

| Material | |
|-----------------|---------|
| Housing | Easylen |
| Color | black |

| Environmental | |
|---|------------------|
| Standards compatibility accotding to UL94 | V0 |
| Protection class | IP65 |
| Temperature range | -25 °C bis +40°C |